

<b>SDI INPUT &amp; OUTPUT FORMATS</b>	3G:SMPTE 424M@2.97 and 2.967Gb/s <ul style="list-style-type: none"> <li>• 1080p@60/59.94/50Hz</li> </ul> HD:SMPTE 292M/274M/296M@1.485 and 1.435Gb/s <ul style="list-style-type: none"> <li>• 1080i@60/59.94/50Hz</li> <li>• 1080p/psf@30/29.97/25/24/23.98Hz</li> <li>• 720p@60/59.94/50/30/29.97/25/24/23.98Hz</li> </ul> SD:SMPTE 259M@270Mb/s <ul style="list-style-type: none"> <li>• 625i50</li> <li>• 525i59.94</li> </ul>	<b>LCD / BUTTON MENU OPTIONS</b>	<ul style="list-style-type: none"> <li>• HDMI output type</li> <li>• Output Select</li> <li>• Multi-Viewer Output Format</li> <li>• Multi-Viewer Number of Windows</li> <li>• Multi-Viewer Layout</li> <li>• Multi-Viewer Audio Source</li> <li>• Multi-Viewer Reference</li> <li>• Full Screen is Scaled</li> <li>• Input Routing</li> <li>• GPI mode</li> <li>• Setup</li> </ul>
<b>HDMI OUTPUT FORMATS</b>	<ul style="list-style-type: none"> <li>• 1080p@60/59.94/50Hz</li> <li>• 1080i@60/59.94/50Hz</li> <li>• 1080p@30/29.97/25/24/23.98Hz</li> <li>• 720p@60/59.94/50/30/29.97/25</li> <li>• 625i50</li> <li>• 525i59.94</li> </ul>	<b>INPUTS</b>	<ul style="list-style-type: none"> <li>• 16 x (3G/HD/SD)-SDI</li> <li>• Input Equalization &gt; 100M using Belden 1694A</li> <li>• USB for control and updates</li> </ul>
<b>POWER</b>	<ul style="list-style-type: none"> <li>• +5V to +32V DC</li> <li>• Positive Centre Pin</li> </ul>	<b>OUTPUTS</b>	<ul style="list-style-type: none"> <li>• HDMI Type A</li> <li>• 1 x SDI (3G/HD/SD)-SDI</li> </ul>
<b>DIMENSIONS</b>	220mm x 103.7mm x 29.5mm (8.7" x 4.1" x 1.2")		